

4'x6'x12" Fail-Safe MilBerm

Product Images



Clean lines of the berm with no obstruction either on the berm interior or exterior.



Fail-Safe® flotation device on both the entry and exit walls is self-erecting and will rise as the fluid level rises. The entry/exit walls also have the brace support, which will lock into position with the rising fluid level.

Patented support mechanism



Sets up to a 90° locked position. Integrated holes in hub permit easy anchoring.



Stainless steel support is encased in protective hub to withstand vehicle traffic.



Fail-Safe® MilBerm™					
NSN	Description	Application	Capacity	CA Prop 65	
4235-01-387-1381	Fail-Safe® MilBerm™ 4 ft x 6 ft x 1 ft	Small generators/ POL storage	179 gal	⚠	
4235-01-387-1498	Fail-Safe® MilBerm™ 10 ft x 10 ft x 1 ft	15K-60K generators/ POL storage	748 gal	⚠	
4235-01-670-1849	Fail-Safe® MilBerm™ 10 ft x 16 ft x 1 ft	100K generators/ POL storage	1196 gal	⚠	
4235-01-569-8818	Fail-Safe® MilBerm™ 12 ft x 26 ft x 1 ft	5 and 7 ton with fuel pods	2333 gal	⚠	
4235-01-569-8792	Fail-Safe® MilBerm™ 12 ft x 30 ft x 1 ft	5 or 7 ton with fuel pods	2692 gal	⚠	
4235-01-569-8833	Fail-Safe® MilBerm™ 12 ft x 36 ft x 1 ft	HEMITT 2,500 gallon fuel tanker and FRC	3231 gal	⚠	
4235-01-550-3802	Fail-Safe® MilBerm™ 14 ft x 54 ft x 1 ft	5,000 gallon tanker	5654 gal	⚠	
4235-01-569-8848	Fail-Safe® MilBerm™ 14 ft x 56 ft x 1 ft	5,000 gallon tanker	5864 gal	⚠	

⚠WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm, and nickel, which is known to the state of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Short Description

Fail-Safe® MilBerm™

Heavy-duty construction provides long-term spill containment for vehicles, heavy equipment, tankers, generators, and more

- Single-piece construction—patented wall-support system integral to berm provides unobstructed work space
- Provides faster deployment—stronger structural integrity
- Quick and easy setup—no assembly required
- Heavy-duty BC3CF fabric stands up to corrosive solvents and extended wear
- Fail-Safe® flotation device on entry/exit walls, enabling drive-in and drive-out with no need to raise or lower wall
- When in the upright and locked position, wall supports prevent snow and ice from interfering during a spill occurrence

Specifications

SKU	1055-02003
Brand	BCI
Net Weight, lbs	24
Net Weight, kgs	10.872